

MX40 - 230V

- Combining cutting-edge technology with elegant modern design, the MX25 offers fast, hassle-free installation and maintenance thanks to its separate mounting base, into which also the power supply is connected.
- It can be mounted ceiling or wall and used as 1 or 2 sided.

CE	0-55°C	LED	1H/3H	EN-STANDARDS EN 60598-2-22 EN 1838 EN 62034 EN ISO 7010
IP 41	40M	-O-	230V	

Technical information:

- Viewing distance: 40m
- Supply voltage: 220-240V
- Light Source: LED
- Input power: 0,8W
- Charging battery: 1,77W
- Insulation class: II
- Battery: Ni-MH 1.2V / 1h, 2.4V / 3h
- IP Class: 41
- Colour: RAL
- Material: PC, Acryl
- Temperature range: 0 - +55 C°



Product No.	Name	Viewing distance	Supply Voltage	Sign	Battery	Backup (h)
840122	MX40 230V AT 1h w	40m	230 VAC	Left, Right, Up, Down	NiMh 1.2V	1h
840124	MX40 230V AT BLACK 1h	40m	230 VAC	Left, Right, Up, Down	NiMh 1.2V	1h
840323	MX40 230V AT 3h w	40m	230 VAC	Left, Right, Up, Down	NiMh 2.4V	3h
840324	MX40 230V AT BLACK 3h	40m	230 VAC	Left, Right, Up, Down	NiMh 2.4V	3h

INSTALLATION PICTOGRAM

